



ESPECIFICACIONES

CUADRO	
TALLAS	S, M, L, XL
COLORES	Phantom Green / Black / Chrome,
CUADRO	ALUXX SL-Grade Aluminum front and rear triangles, 120mm Maestro suspension, flip chip, 12x148mm thru-axle
HORQUILLA	Fox 34 Performance, 130mm, GRIP damper, Boost 15x110 Kabolt, 44mm offset, custom tuned for Giant
AMORTIGUADOR	Fox Float DPS Performance, 185/50, custom tuned for Giant
COMPONENTES	
MANILLAR	Giant Contact TR35, 780x35mm
GRIPS	Giant Tactal Pro Single S:120mm, M:120mm, L:130mm, XL:130mm
POTENCIA	Giant Contact SL 35 S:40mm, M:40mm, L:50mm, XL:50mm
TIJA DE SILLÍN	Giant Contact Switch dropper, remote S: 125mm travel / 30.9 x 395mm M: 150mm travel / 30.9 x 440mm L: 170mm travel / 30.9 x 450mm XL: 170mm travel / 30.9 x 450mm
SILLÍN	Giant Romero
PEDALES	N/A
TRANSMISIÓN	
MANETAS DE CAMBIO	Shimano SLX SL-M7100, 1x12
DESVIADOR	N/A
CAMBIO TRASERO	Shimano SLX RD-M7100
FRENOS	Shimano Deore BR-MT520, hydraulic, Shimano RT-56 rotors [F]180mm, [R]180mm
PALANCAS DE FRENOS	Shimano BL-MT501
CASSETTE	Shimano SLX, 10x51
CADENA	KMC X-12
JGO. PLATOS Y BIELAS	Shimano SLX, 30t S:165mm, M:170mm, L:170mm, XL:170mm
CAJA DE PEDALIER	Shimano, press fit
RUEDAS	
LLANTAS	Giant AM 29 tubeless ready sleeve-joint rim, 30mm inner width
BUJES	alloy, sealed
RADIOS	Sapim
CUBIERTAS	[F] Maxxis Minion DHF 29x2.5 WT, 3C MaxxTerra, EXO, TR [R] Maxxis Aggressor 29x2.5, EXO, TR, tubeless
EXTRAS	tubeless prepared, 2.6" max tire size, 34t max chainring size

CARACTERÍSTICAS

- Cuadro: ALUXX SL-Grade Aluminum front and rear triangles, 120mm Maestro suspension, flip chip, 12x148mm thru-axle
- Horquilla: Fox 34 Performance, 130mm, GRIP damper, Boost 15x110 Kabolt, 44mm offset, custom tuned for Giant
- Manetas de cambio: Shimano SLX SL-M7100, 1x12
- Jgo. platos y bielas: Shimano SLX, 30t S:165mm, M:170mm, L:170mm, XL:170mm
- Colores: Phantom Green / Black / Chrome,

Precio: PVP 3.599 €

GEOMETRÍA

CUADRO	S		M		L		XL	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Longitud del tubo del sillín (mm)	420	430	465	496				
Ángulo del tubo del sillín	77,2° 78,0°	76,3° 77,0°	76,3° 77,0°	76,3° 77,0°	76,3° 77,0°	76,3° 77,0°	76,3° 77,0°	76,3° 77,0°
Longitud del tubo superior (mm) (mm)	561 559	599 597	626 624	663 661				
Longitud del tubo de dirección (mm) (mm)	100	110	120	130				
Ángulo del tubo de dirección	65,4° 66,2°	65,5° 66,2°	65,5° 66,2°	65,5° 66,2°	65,5° 66,2°	65,5° 66,2°	65,5° 66,2°	65,5° 66,2°
Inclinación de la horquilla (mm)	44	44	44	44				
Trail (mm) (mm)	126 120	126 120	126 120	126 120				
Distancia entre ejes (mm) (mm)	1166 1165	1195 1194	1224 1223	1263 1262				
Longitud de la vaina (mm) (mm)	439 437	439 437	439 437	439 437				
Caída de la caja de pedalier (mm) (mm)	45 35	45 35	45 35	45 35				
Stack (mm) (mm)	610 604	619 613	628 622	637 631				
Reach (mm) (mm)	422 431	447 456	472 480	507 515				
Altura del suelo al tubo (mm) (mm)	730 738	725 734	749 759	771 780				
Ancho del manillar (mm) (mm)	780	780	780	780				
Longitud de la potencia (mm) (mm)	40	40	50	50				
Longitud de las bielas (mm) (mm)	165	170	170	170				
Tamaño de ruedas	29"	29"	29"	29"				

Giant se reserva el derecho a modificar especificaciones, precios o colores sin previo aviso.